



## BELLINA CERAMIC TILE



3" x 13" BELLINA GREY BULLNOSE  
BFC313BBNG



3" x 8" BELLINA GREY BULLNOSE  
BFC38BBNG



13" x 13" BELLINA GREY FLOOR TILE  
BFC1313BG



8" x 10" BELLINA GREY WALL TILE  
BFC810BG



2" x 2" BELLINA MULTI MOSAICS  
BFC22BM

## BELLINA CERAMIC TILE



3" x 13" BELLINA CREAM BULLNOSE  
BFC313BBNC



3" x 8" BELLINA CREAM BULLNOSE  
BFC38BBNC



13" x 13" BELLINA CREAM FLOOR TILE  
BFC1313BC



8" x 10" BELLINA CREAM WALL TILE  
BFC810BC

## BELLINA CERAMIC TILE

### PACKAGING INFORMATION

DESCRIPTION	ITEM CODE		LBS/BOX	PCS/BOX	SQFT/BOX	BOXES/SKID	SQFT/SKID
	GREY	CREAM					
8" x 10" BELLINA WALL TILE	BFC810BG	BFC810BC	26.28	20	10.76	92	989.92
13" x 13" BELLINA FLOOR TILE	BFC1313BG	BFC1313BC	44.19	11	12.91	58	748.90
3" x 8" BELLINA BULLNOSE	BFC38BBNG	BFC38BBNC	12.81	30	n/a	105	3150 pcs.
3" x 13" BELLINA BULLNOSE	BFC313BBNG	BFC313BBNC	20.83	21	n/a	84	1764 pcs.
2" x 2" BELLINA MULTI MOSAICS	BFC22BM		39.33	10	11.74	48	563.52

### GENERAL SPECIFICATIONS

DESCRIPTION	METHOD	UNIT	13" x 13"
THICKNESS		mm – in	7.6 mm – 5/16"
WATER ABSORPTION	EN ISO 10545-3	( % )	≤ 3
ABRASION RESISTANCE	EN ISO 10545-7	(PEI)	3
SCRATCH HARDNESS		(Mohs)	5
BREAKING STRENGTH	EN ISO 10545-4	(lbf)	≥ 250
CHEMICAL RESISTANCE	EN ISO 10545-13	(GL)	Class A – Resistant
FROST RESISTANCE	EN ISO 10545-12		Resistant
STATIC COEFFICIENT OF FRICTION (WET)	ASTM C-1028	(μ)	< 0.60
STATIC COEFFICIENT OF FRICTION (DRY)	ASTM C-1028	(μ)	≥ 0.90
DCOF (WET)	ANSI B101.3		< 0.42
SHADE VARIATION			V2